

## Product information

# 97 53 14

## Self-Adjusting Crimping Pliers for wire ferrules

With lateral access



- Narrow handle width and improved ergonomics
- For crimping wire ferrules according to DIN 46228 parts 1 + 4
- Self-adjustment to the size of wire ferrules required
- Repetitive, high crimping quality due to integral lock (self-releasing mechanism)
- Tools have been set precisely (calibrated) in the factory
- Optimum transmission of force thanks to toggle lever for fatigue-reduced operation
- Handy shape and low weight provide high operation comfort
- Expanded capacity of hexagonal crimping up to 10 mm<sup>2</sup>
- Hexagonal compression for confined connection dimensions
- Suitable in particular for all twin wire ferrules up to 2 x 4 mm<sup>2</sup> or 2 x AWG 10
- Chrome vanadium electric steel in special quality, oil-hardened



| General                        |                            |
|--------------------------------|----------------------------|
| Article No.                    | 97 53 14                   |
| EAN                            | 4003773041474              |
| Pliers                         | burnished                  |
| Handles                        | with multi-component grips |
| weight                         | 445 g                      |
| Dimensions                     | 180 x 75 x 21 mm           |
| Technische Attribute           |                            |
| Applications                   | Wire ferrules              |
| Capacity in square millimetres | 0.08 — 10 mm <sup>2</sup>  |
| Number of crimping positions   | 1                          |
| AWG                            | 28 — 7                     |
| Classification                 |                            |
| eCl@ss 5.1.4                   | 21040301                   |
| ETIM 5.0                       | EC000168                   |
| ETIM 6.0                       | EC000168                   |
| proficl@ss 6.0                 | AAA946c003                 |
| UNSPSC 13.1                    | 27112147                   |

*technical change and errors excepted*